

Sheet1

MAPLE.ABS patch to change from port 330Q to 340Q

1. Copy MAPLE.ABS to a single sided floppy as MAPLE340.ABS.
2. Run DUMP MAPLE340.ABS and record the Disk Track and Sector numbers.
3. Run DUMP and specify the Drive, Track and Sector.
4. Verify that the data exists at the coordinate specified below and, if so, edit.
5. Change each value for the sector.
6. Verify that the data is correct and, if so, write the sector back to disk.

Disk Track	Sequential Sector #	Coord	330 Orig	340 New	Disk Track	Sequential Sector #	Coord	330 Orig	340 New
	6	76	D8	E0		21	40	D9	E1
							45	DC	E4
	7	C2	D9	E1					
		C4	DC	E4		22	B5	D9	E1
		C9	DC	E4					
		CB	DB	E3		23	1B	D9	E1
		D0	DB	E3					
		D3	D8	E0		25	1E	DD	E5
		D6	D9	E1			31	D8	E0
		D9	DB	E3			67	DE	E6
		DB	D8	E0			6C	DE	E6
		E0	D8	E0					
		E3	DC	E4		26	7B	E0	E8
		F4	DB	E3			C6	DD	E5
		FC	DB	E3			CB	D8	E0
	8	00	DB	E3		28	13	DD	E5
		20	DB	E3			1B	D8	E0
		28	DB	E3			A1	D9	E1
		2C	DB	E3			A7	D9	E1
							BB	D9	E1
	10	26	DD	E5					
		2E	D9	E1		29	09	DB	E3
		30	DB	E3			0E	DB	E3
		35	DB	E3					
		3B	DB	E3		30	9A	D8	E0
						37	E1	DC	E4